

## GS-702S-RN6A

### 6MP Outdoor AI POE Bullet Camera



The GS-702S-RN6A 6MP Outdoor AI POE Bullet Camera provides high definition analog output. It supports H.265+ video compression, which assures savings in bandwidth and storage.

8PCS Warm LED provides a good interface and good effective for night vision.

The 4mm lens can view angles that fit any situation. D-WDR (Digital-Wide Dynamic Range) and 3D-DNR ensure that ideal images are in good conditions for both day and night vision.

- 6MP High Performance CMOS
- Up to 3072\*2048 Resolution
- 4mm
- 8PCS Warm LED
- Internal PoE
- ONVIF 2.4
- Multi-Platform Monitoring
- Supports 3D DNR/AWB/Exposure
- Metal Housing
- IP67




# Specifications

GS-702S-RN6A	
Camera	
Image Sensor	6.0 MP CMOS IMX464
Signal System	PAL/NTSC
Effective Resolution	3072H*2048V
Minimum Illumination	0.1lux, 0 lux with IR
Shutter Speed	AUTO/ 1/25-1/10000sec
Lens	4 mm (2.8/6 mm optional)
Horizontal Field of View	82.6° (3.6 mm), 54.4° (6 mm)
Day/Night	Support D/N switching (IR-CUT optional)
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°
WDR	D-WDR
White balance	Support auto white balance
Image Enhancement	3N-DNR/D-WDR/BLC/HLC
General Function	Mirror, Privacy shelter, Human Detection, Voice recording, Restart
OSD	Support OSD setting, drag the position freely
Intelligent function	
Human detection	It supports human detection and can detect human shape for intelligent
Voice Announcements	Support voice broadcast after human detection.
Light alarm	Support linkage light alarm when human form is detected.
Video	
Compression	H.264, H.265
Main stream	6MP(3072*2048)
Sub-stream	448P(800*448)
Frame rate	5MP 20fps, 4MP 25fps, 3MP 30fps
Video Adjustment	Brightness, saturation, chroma, contrast and sharpness adjustment
Network	
Ethernet	RJ-45 10M/100M self-adaption
Protocol	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS, IP
Access protocol	Support ONVIF/private protocol/CGI
User/Host	Up to 4 users
Client	IOS, Android, Windows
Interface	
Communication Interface	1-port RJ45 10M/100M self-adaptive Ethernet port
On-Board Storage	N/A
Reset Button	N/A
General	
Operating Conditions	-4° F to 140° F (-20° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12V DC
Power Consumption	Maximum: 6 W
IR Range	Up to 65 ft (20 m)
Protection Level	IP67
Communication	Up-the-Coaxial
Dimensions	233 mm x 75 mm x 68 mm
Weight	Approximately 0.6 kg

## Dimensions

---



© SHENZHEN GRANDSECU TECHNOLOGY CO., LTD • All Rights Reserved • Specifications subject to change without notice.

Address: No.11 Xiantian Road, Xinsheng Community, Longgang District, Shenzhen, China 518116

Tel: +86-755-2851-0749 • E-Mail: [info@grandsecu.cn](mailto:info@grandsecu.cn) • Website: [www.grandsecu.cn](http://www.grandsecu.cn)

**GRANDSECU®**