

## GS-K631-RP5A

### 5MP Outdoor AI IPC Full Color Bullet Camera POE



#### Features

- 5MP High Performance CMOS
- Up to 2880\*1624 Resolution
- 3.6 mm Lens
- 6 PCS Warm LED
- ONVIF 2.4
- Multi-Platform Monitoring
- Supports 3D DNR/AWB/Exposure
- Full color night vision
- Metal housing
- IP67

The GS-K631-RP5A 5MP Outdoor AI IPC Full Color Bullet Camera provides high definition output. It supports H.265+ video compression, which assures savings in bandwidth and storage.

6 PCS Warm led provides a good interface and good effective for color vision.

The 3.6mm lens is optimized for viewing angles that fit any situation. D-WDR (Digital-Wide Dynamic Range) and 3D-DNR ensure that ideal images are in good conditions for both day and night vision.



## SPECIFICATIONS

Camera	
Image Sensor	5.0 MP CMOS GC4653
Signal System	IPC
Effective Resolution	2880H*1624V
Minimum Illumination	0.1lux, 0 lux with IR
Shutter Speed	AUTO/ 1/25-1/10000sec
Lens	3.6 mm (2.8/6 mm optional)
Horizontal Field of View	82.6° (3.6 mm), 54.4° (6 mm)
Day/Night	Support D/N switching (IR-CUT optional) and full color option
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°
WDR	D-WDR
White balance	Support auto white balance
Image Enhancement	3N-DNR/D-WDR/BIC/HIC
General Function	Mirror, Privacy shelter, Human Detection , Restart
OSD	Support OSD setting, drag the position freely
Intelligent function	
Human detection	It supports human detections
Light alarm	Support linkage light alarm when human form is detected.
Video	
Compression	H.264 , H.265
Main stream	5MP (2880*1624)
Sub-stream	448P (800*448)
Frame rate	5MP 20fps, 4MP 25fps , 3MP 30fps
Video Adjustment	Brightness, saturation, chroma, contrast and sharpness adjustment

Network	
Ethernet	RJ-45 10M/100M self-adaption
Protocol	ONVIF , P2P , CGI , HTTP , TCP/IP , IPv4 , RTSP , UDP , NTP , DHCP , DNS , IP
Access protocol	Support ONVIF/private protocol/CGI
User/Host	Up to 4 users
Client	IOS , Android , Windows
Interface	
Communication Interface	1-port RJ45 10M/100M self-adaptive Ethernet port
On-Board Storage	N/A
Reset Button	N/A
General	
Operating Conditions	-4° F to 140° F (-20° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12V DC – or POE
Power Consumption	Maximum: 6 W
IR Range	Up to 65 ft (20 m)
Protection Level	IP67
Communication	RJ45
Dimensions	185 mm x 58 mm x 70 mm
Weight	Approximately 0.35 kg

