

GS-616-RA5I

5MP Indoor 4 in 1 Full color Dome Camera



The GS-616-RA5I 5MP Indoor 4 in 1 Full color Dome Camera provides high definition analog output. AHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

6PCS Warm LED provides a good interface and good effective for night vision.

The 1.8 mm lenses are optimized for viewing angles that fit any situation. D-WDR (Digital-Wide Dynamic Range) and 2D-DNR ensure that ideal images are in good conditions for both day and night vision.

- 5MP High Performance CMOS
- Up to 2608*1952 Resolution
- AHD/TVI/CVI/CVBS 4 in 1 Output
- 1.8 mm Lens
- 6PCS Warm LED
- Full color night vision
- Up-the-Coax (supports UTC)
- Supports 2D DNR/AWB/Exposure
- Metal Housing
- IP66



Specifications

| GS-616-RA5I | |
|--------------------------|---|
| Camera | |
| Image Sensor | 5.0 MP CMOS S0I K05 |
| Signal System | PAL/NTSC |
| Effective Resolution | 2608H*1952V |
| Frame Rate | 5mp @ 12.5 fps/20 fps |
| Minimum Illumination | 0.2lux, 0 lux with IR |
| Shutter Speed | AUTO/1/50 (1/60) -1/50,000sec |
| Lens | 1.8 mm |
| Horizontal Field of View | 120° (1.8 mm), |
| Day/Night | Auto/color/BW (Black and White) |
| Angle Adjustment | Pan/ Rotate:0° to 360°; Tilt: 0° to 75° |
| WDR | D-WDR |
| Menu | |
| AGC | Supported |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| White Balance | AUTO/MANUAL |
| Privacy Mask | ON/OFF, 8 programmable privacy masks |
| Motion Detection | 4 programmable motion areas |
| Backlight Compensation | D-WDR/BLC/HLC/off |
| 2D and 3D DNR | On/off |
| Voltage Detection | Supported |
| Scene | Indoor/outdoor/hard light/low light |
| Functions | Mirror, Defective pixel correction, Sharpness, Camera title |
| Interface | |
| Video Output | 1CH AHD/TVI/CVI/CVBS 4 in 1 Output |
| General | |
| Operating Conditions | -4° F to 140° F (-20° C to 60° C), humidity: 90% or less (non-condensation) |
| Power Supply | 12V DC |
| Power Consumption | Maximum: 6 W |
| IR Range | Up to 65 ft (20 m) |
| Protection Level | IP66 |
| Communication | Up-the-Coax |
| Dimensions | φ109 mm x 109 mm |
| Weight | Approximately 0.5 kg |

Dimensions

© SHENZHEN GRANDSECU TECHNOLOGY CO., LTD • All Rights Reserved • Specifications subject to change without notice.
Address: No.11 Xiantian Road, Xinsheng Community, Longgang District, Shenzhen, China 518116
Tel: +86-755-2851-0749 • E-Mail: info@grandsecu.cn • Website: www.grandsecu.cn

GRANDSECU®