

## GS-701S-RH4D

### 8MP Outdoor AI IPC FULL COLOR Bullet Camera



The GS-701S-RH4D 8MP Outdoor AI IPC FULL COLOR Bullet Camera provides high definition output. It supports H.265+ video compression, which assures savings in bandwidth and storage.

8PCS smart dual LED provides a good interface and good effective for night vision.

The 2.7-13.5mm AF lenses can 4X AF Optical Zoom for viewing angles that fit any situation. D-WDR (Digital-Wide Dynamic Range) and 3D-DNR ensure that ideal images are in good conditions for both day and night vision.

- 8MP High Performance CMOS
- Up to 3264\*2448 Resolution
- 2.7-13.5mm AF LENS
- 8PCS smart dual LED
- ONVIF 2.4
- Multi-Platform Monitoring
- Supports 3D DNR/AWB/Exposure
- Full color night vision



## Specifications

| GS-701S-RH4D             |  |
|--------------------------|--|
| Camera                   |  |
| Image Sensor             | 8.0 MP IMX415  |
| Signal System            | PAL/NTSC   |
| Effective Resolution     | 3264H*2448V  |
| Minimum Illumination     | 0.1lux, 0 lux with IR                                      |
| Shutter Speed            | AUTO/ 1/25-1/10000sec                                      |
| Lens                     | 2.7-13.5mm AF lens   |
| Horizontal Field of View | 82.6° (3.6 mm), 54.4° (6 mm)                               |
| Day/Night                | Support D/N switching (IR-CUT optional)                    |
| Angle Adjustment         | Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°       |
| WDR                      | D-WDR  |
| White balance            | Support auto white balance                                 |
| Image Enhancement        | 3N-DNR/D-WDR/BLC/HLC                                       |
| General Function         | Mirror, Privacy shelter, Human Detection, Restart          |
| OSD                      | Support OSD setting, drag the position freely              |
| Intelligent function     |  |
| Human detection          | It supports human detection and can detect human shape for |
| Light alarm              | Support linkage light alarm when human form is detected.   |
| Video                    |  |
| Compression              | H.264 , H.265  |

|                         |   |
|-------------------------|---|
| Main stream             | 8MP(3264*2448)  |
| Sub-stream              | 448P(800*448)   |
| Frame rate              | 8MP 20fps, 5MP 25fps , 3MP 30fps  |
| Video Adjustment        | Brightness, saturation, chroma, contrast and sharpness adjustment           |
| <b>Network</b>          |   |
| Ethernet                | RJ-45 10M/100M self-adaption  |
| Protocol                | ONVIF , P2P , CGI , HTTP , TCP/IP, IPv4 , RTSP , UDP , NTP , DHCP , DNS, IP |
| Access protocol         | Support ONVIF/private protocol/CGI  |
| User/Host               | Up to 4 users   |
| Client                  | IOS , Android , Windows   |
| <b>Interface</b>        |   |
| Communication Interface | 1-port RJ45 10M/100M self-adaptive Ethernet port                            |
| On-Board Storage        | N/A   |
| Reset Button            | N/A   |
| <b>General</b>          |   |
| Operating Conditions    | -4° F to 140° F (-20° C to 60° C), humidity: 90% or less (non-condensation) |
| Power Supply            | 12V DC  |
| Power Consumption       | Maximum: 6 W  |
| IR Range                | Up to 65 ft (20 m)  |
| Protection Level        | IP66  |
| Communication           | Up-the-Coaxial  |
| Dimensions              | 155 mm x 59 mm x 67 mm  |
| Weight                  | Approximately 0.35 kg   |

## Dimensions

