

HD564E-A0/K03

5MP Outdoor 4 in 1 Full color Bullet Camera



- 5MP High Performance CMOS
- Up to 2608*1952 Resolution
- AHD/TVI/CVI/CVBS 4 in 1 Output
- 3.6 mm Lens
- 6PCS Warm LED
- Full color night vision
- Up-the-Coax (supports UTC)
- Supports 2D DNR/AWB/Exposure
- Metal+Plastic Housing
- IP66

The HD564E-A0/K03 5MP Outdoor 4 in 1 Full color Bullet Camera provides high definition analog output. AHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

6PCS Warm LED provides a good interface and good effective for night vision.

The 3.6 mm lens is optimized for viewing angles that fit any situation. D-WDR (Digital-Wide Dynamic Range) and 2D-DNR ensure that ideal images are in good conditions for both day and night vision.



Specifications

| HD564E-A0/K03 | |
|--------------------------|-----------------------------------------------------------------------------|
| Camera | |
| Image Sensor | 5.0 MP CMOS SOI K03 |
| Signal System | PAL/NTSC |
| Effective Resolution | 2608H*1952V |
| Frame Rate | 5mp @ 12.5 fps/20 fps |
| Minimum Illumination | 0.2lux, 0 lux with IR |
| Shutter Speed | AUTO/ 1/50 (1/60) -1/50,000sec |
| Lens | 3.6 mm (2.8/6 mm optional) |
| Horizontal Field of View | 82.6° (3.6 mm), 54.4° (6 mm) |
| Day/Night | Auto/color/BW (Black and White) |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360° |
| WDR | D-WDR |
| Menu | |
| AGC | Supported |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| White Balance | AUTO/MANUAL |
| Privacy Mask | ON/OFF, 8 programmable privacy masks |
| Motion Detection | 4 programmable motion areas |
| Backlight Compensation | D-WDR/BLC/HLC/off |
| 2D and 3D DNR | On/off |
| Voltage Detection | Supported |
| Scene | Indoor/outdoor/hard light/low light |
| Functions | Mirror, Defective pixel correction, Sharpness, Camera title |
| Interface | |
| Video Output | 1CH AHD/TVI/CVI/CVBS 4 in 1 Output |
| General | |
| Operating Conditions | -4° F to 140° F (-20° C to 60° C), humidity: 90% or less (non-condensation) |
| Power Supply | 12V DC |
| Power Consumption | Maximum: 6 W |
| IR Range | Up to 65 ft (20 m) |
| Protection Level | IP66 |
| Communication | Up-the-Coax |
| Dimensions | 176.5mm x 54.67 mm x 68 mm |
| Weight | Approximately 0.35 kg |

© SHENZHEN GRANDSECU TECHNOLOGY CO., LTD - All Rights Reserved - Specifications subject to change without notice.

Address: No.11 Xiantian Road, Xinsheng Community, Longgang District, Shenzhen, China 518116

Tel: +86-755-2851-0749 - E-Mail: info@grandsecu.cn - Website: www.grandsecu.com.cn

GRANDSECU[®]