

GS-K635-RA8G

8MP Outdoor 4 in 1 Full Color Bullet Camera



The GS-K635-RA8G 8MP Outdoor 4 in 1 Full Color Bullet Camera provides high definition analog output. AHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

4PCS Warm LED provides a good interface and good effective for night vision.

The 4 mm lenses are optimized for viewing angles that fit any situation. 2D-DNR ensure that ideal images are in good conditions for both day and night vision.

- 8MP High Performance CMOS
- Up to 3840*2160 Resolution
- AHD/TVI/CVI/CVBS 4 in 1 Output
- 4 mm Lens
- 4PCS Warm LED
- Full color night vision
- Up-the-Coax (supports UTC)
- Supports 2D DNR/AWB/Exposure
- IP66



Specifications

GS-K635-RA8G	
Camera	
Image Sensor	8.0 MP CMOS C18
Signal System	PAL/NTSC
Effective Resolution	3840H*2160V
Frame Rate	8mp @ 15 fps
Minimum Illumination	0.2lux, 0 lux with IR
Shutter Speed	AUTO/ 1/50 (1/60) -1/50,000sec
Lens	4mm
Horizontal Field of View	82.6° (3.6 mm), 54.4° (6 mm)
Day/Night	Auto/color/BW (Black and White)
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°
WDR	D-WDR
Menu	
AGC	Supported
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	AUTO/MANUAL
Privacy Mask	ON/OFF, 8 programmable privacy masks
Motion Detection	4 programmable motion areas
Backlight Compensation	BLC/HLC/off
2D and 3D DNR	On/off
Voltage Detection	Supported
Scene	Indoor/outdoor/hard light/low light
Functions	Mirror, Defective pixel correction, Sharpness, Camera title
Interface	
Video Output	1CH AHD/TVI/CVI/CVBS 4 in 1 Output
General	
Operating Conditions	-4° F to 140° F (-20° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12V DC
Power Consumption	Maximum: 6 W
IR Range	Up to 65 ft (20 m)
Protection Level	IP66
Communication	Up-the-Coax
Dimensions	183 mm x 65 mm x 58mm
Weight	Approximately 0.35 kg