

GS-K771-RH5D

5MP Outdoor AI IPC POE SMART LIGHT Bullet Camera



The GS-K771-RH5D 5MP Outdoor AI IPC SMART LIGHT Bullet Camera provides high definition analog output. It supports H.265+ video compression, which assures savings in bandwidth and storage.

4PCS White LED provides a good interface and good effective for night vision.

The 3.6 mm lenses are optimized for viewing angles that fit any situation. D-WDR (Digital-Wide Dynamic Range) and 3D-DNR ensure that ideal images are in good conditions for both day and night vision.

- 5MP High Performance CMOS
- Up to 2880*1620 Resolution
- 3.6 mm Lens
- 4PCS White LED
- Support POE
- ONVIF 2.4
- Multi-Platform Monitoring
- Supports 3D DNR/AWB/Exposure
- Smart Black light night vision
- Metal Housing
- IP66



Specifications

GS-K771-RH5D	
Camera	
Image Sensor	5.0 MP CMOS
Signal System	PAL/NTSC
Effective Resolution	2880*1620
Minimum Illumination	0.1lux, 0 lux with IR
Shutter Speed	AUTO/1/25-1/10000sec
Lens	3.6 mm
Horizontal Field of View	82.6°(4 mm)
Day/Night	Support D/N switching (IR-CUT optional)
WDR	D-WDR
White balance	Support auto white balance
Image Enhancement	3N-DNR/D-WDR/BLC/HLC
General Function	Mirror, Privacy shelter, Human Detection, Restart
OSD	Support OSD setting, drag the position freely
Intelligent function	
Human detection	It supports human detection and can detect human shape for intelligent
Voice Announcements	Support voice broadcast after human detection.
Light alarm	Support linkage light alarm when human form is detected.
Video	
Compression	H264, H265
Main stream	5MP(2880*1620)
Sub-stream	448P(800*448)
Frame rate	5MP 30fps
Video Adjustment	Brightness, saturation, chroma, contrast and sharpness adjustment
Network	
Ethernet	RJ-45 10M/100M self-adaption
Protocol	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS, GB28181
Access protocol	Support ONVIF/private protocol/CGI
User/Host	Up to 4 users
Client	IOS, Android, Windows
Interface	
Communication Interface	1-port RJ45 10M/100M self-adaptive Ethernet port
On-Board Storage	N/A
Reset Button	N/A
General	
Operating Conditions	-4°F to 140°F (-20°C to 60°C), humidity: 90% or less (non-condensation)
Power Supply	12V DC/48V POE
Power Consumption	Maximum: 6 W
IR Range	Up to 65 ft (20 m)
Protection Level	IP66

Dimensions

© SHENZHEN GRANDSECU TECHNOLOGY CO., LTD • All Rights Reserved • Specifications subject to change without notice.
 Address: No.11 Xiantian Road, Xincheng Community, Longgang District, Shenzhen, China 518116
 Tel: +86-755-2851-0749 • E-Mail: info@grandsecu.cn • Website: www.grandsecu.com.cn