

## GS-X16-RX5A (5MP) P6SLite Camera



- **HD image for 360° Fullview**
- **Cloud storage/256GB TF card storage**
- **WiFi Hotspot**
- **dual light infrared led, night function**
- **Sleep Mode for privacy protection**
- **P6S Protocol for NVR connection**
- **ONVIF 2.4**
- **Accurate Human Detection and Tracking**

H265 encoding, lower bit rate, clearer image quality, less bandwidth occupied, longer storage time of TF card.

Support accurate humanoid detection alarm function, greatly reduce false alarms, support police linkage trigger email, trigger FTP, trigger SD card capture, support alarm trigger SD card recording, cloud recording and sound and light alarm and other functions.

Support preset bit setting, up to 6 preset.

Support humanoid tracking function, support guard position function, after the target tracking is completed, it can automatically return to the guard position, support position calibration function.

Support HUAWEI CLOUD service, APP without ad pop-up window.

APP supports 17 kinds language. (Chinese Simplified/Chinese/Traditional/English/Finnish/Korean/French/Portuguese/Thai/Spanish/Polish/Indonesian/German/Italian/Russian/Japanese/Vietnamese/Arabic/Turkish).



# Specifications

## GS-X16-RX5A

Camera	
Model	GS-X16-RX5A
Main processor	P5AU
Operating system	Embedded LINUX operating system
Video	
Imaging devices	1/2.9 CMOS Sensor
Video encoding standards	H.265
System format	PAL 50HZ/NTSC 60HZ
Effective resolution	2560*1920 (5MP)
Video frame rate	15fps
Video streaming	135kbps-2048kbps
Minimum illuminance	Day mode 1Lux,night mode0.01Lux
Day and night mode	Auto
Video output	EasyVMS client/Mobile APP client
Capture function	Support
Recording management	
Recording mode	Mobile video, alarm video, timed video, humanoid video
Video saving	TF card/PC/NVR
Cloud storage	backing
Alarm	
Alarm detection	Accurate humanoid detection with low false alarm rate
Sound and light alarm	Yes, when equipped with dual light board, support sound and light alarm
Alarm voice	Support text-to-speech and custom speech functions
Alarm linkage	Linkage video recording, capture image send email and upload FTP server
Gimbal	
Preset bits	Supports 6 preset bit settings
Trace function	Support humanoid tracking, can set the guard position, the target tracking can be completed automatically back to the guard position
Internet	
WIFI	2.4G antenna support, 802.11b/g/n
agreement	ONVIF, P6S
Call	
One-click call	Yes, when calling, you can push pictures to the APP
Sleep	
Sleep function	Supports scheduled sleep and immediate sleep functions to maintain user privacy
Other	
TF card capacity	Supports up to 256GB (universal FAT32 format)
Operating voltage	USB 5V
Video recordings take up space	8GB video recording approx. 45.7 hours (prv format/H.265)
Work environment	-10℃ --- 45℃
General	
Dimensions	75.5mm × 75.5mm × 152mm (with box)
Weight	Approximately 0.31 kg
Carton Meas	405mm × 405mm × 340mm (50pcs/ctn)
Carton Weight	Approximately 16.6 kg

## Di mensi ons

